



255 E. Brown Street, Ste. 100, Birmingham, MI 48009

Phone: 248-433-3500 • Fax: 248-594-3433

Email: sales@permawick.com

http://www.permawick.com

An ISO9001 Certified Company

PD AR465NP

REV. # 3

REV. DATE: March 4, 2015

AR 465NP

Diester Based Synthetic Lubricant for Sintered Metal Bearings

DESCRIPTION

AR465 OIL is a synthetic diester based lubricant formulated to resist gumming and rpm fluctuations and minimize wear. High viscosity index and low pour point indicate excellent low temperature fluidity (-35°C) while providing protection at high temperatures (150°C). AR465 OIL offers protection and reliability over the widest useful temperature range

PRODUCT FEATURES

- Excellent oxidation resistance and corrosion protection
- Very low evaporation rate
- Moderate load carrying
- Reduces friction for low-wear rates
- Outstanding film strength
- Plastic compatible

APPLICATIONS

- Office, business and computer equipment
- Impregnating fluid for powdered metal bearings, parts and wicks
- Anti-friction bearings
- Wire extrusion oil
- Measuring and dispensing pumps and meters
- Mechanical spring and actuator mechanisms
- General purpose medium viscosity lubricant

Performance Test	Test Method	Typical
ISO VG	D2422	68
Specific Gravity	D1298	0.92
Flash Point, °C	D97	261
Pour Point, °C	D92	-55
Viscosity, cSt @ 40°C	D445	58.5
Viscosity, cSt @ 100°C	D445	11.4
Viscosity, cSt @ -30	D445	8000
Viscosity Index	D2270	191
Copper Corrosion, 24 hrs @ 100°C	D130	1a
Four Ball wear, 1200rpm, 75°C, 40Kg, 1hour, mm	D2266	0.8
Four Ball EP Weld Point, Kg	D2783	100
Permawick Blend	Method	Typical
Fiber Content (Wt)	In-House	14 – 19 %
Oil Content (Wt)	In House	81% - 86%
Moisture (%)	ASTM D95	<1.6%