



**PermaWick Company**  
255 E. Brown Street, Suite 100, Birmingham, MI 48009  
Phone: 248-433-3500 • Fax: 248-594-3433  
sales@permaWick.com  
www.permaWick.com

**An ISO9001 Certified Company**

PD 286

REV. # 3

REV. DATE: May 17, 2017

## **286 MINERAL OIL SLEEVE BEARING LUBRICANT**

### **DESCRIPTION**

PERMAWICK 286 OILS are formulated to provide superior performance for sleeve bearings. Solvent extracted and hydro-treated base stocks were selected to give greater oxidation stability and a higher viscosity index. Special oxidation inhibitors have been added to counteract varnish and sludge formation while select anti-wear additives protect against rust, corrosion and wear.

PERMAWICK 286 oils provide the ULTIMATE in performance for sleeve bearings and are definitely the "INDUSTRY STANDARD" in bearing lubrication.

### **PRODUCT FEATURES**

- Extremely long life
- Excellent gear and bearing wear protection
- Low ash
- Shear stable
- Superior low temperature fluidity properties
- Continued protection during periods of high temperature operation
- Useful temperature range: -20°C to 100°C

<b><u>Performance Test: Oil</u></b>	<b><u>ASTM Method</u></b>	<b><u>Typicals</u></b>
Gravity, API	D1298	29.8
Specific gravity	D1298	0.88
Color	D1500	3.0
Flash Point, °C (°F)	D92	215 (495)
Fire Point, °C (°F)	D92	250 (482)
Pour Point, °C (°F)	D97	-30 (-22)
Viscosity, cSt. 40°C	D445	126.6
100°C		15.6
Viscosity Index	D2270	129
Neutralization No., mg KOH/gm	D664	1.5 max
Copper Strip Corrosion, 3 hours @ 212°F	D130	1b max
Evaporation Loss, wt% 22 hours @ 210°F	D972	1.0 max
Rust Protection	D665 A and B	Pass
Falex pin and vee block, lbs	D3233B	1500

**The World Leader in Fractional Horsepower Motor Lubrication**