



PermaWick Company
255 E. Brown Street, Suite 100, Birmingham, MI 48009
Phone: 248-433-3500 • Fax: 248-594-3433
sales@permaWick.com
www.permaWick.com

An ISO9001 Certified Company

PD PHC406

REV. # 2

REV. DATE: June 5, 2017

PHC406 OIL
HYDRO-CRACKED LUBRICANT FOR SINTERED METAL BEARINGS

DESCRIPTION

PERMAWICK HYDRO-CRACKED (PHC) 406 OIL is formulated from a blend of specialty Hydro-treated paraffinic base stocks along with premium additives that provide improved protection against oxidation, corrosion and wear. The hydro-treating process produces high purity base oils that are able to surpass the performance of traditional solvent refined mineral based oils.

PHC 406 oil and the PermaWick products made from it, maximizes FHP electric motor bearing life under a wide variety of conditions while providing excellent value.

PRODUCT FEATURES

- Extremely long life
- Low volatility
- Very shear stable
- Low pour point and naturally high viscosity index
- Superior low temperature performance
- Useful temperature range: -20°C to 110°C

<u>Performance Test</u>	<u>ASTM Method</u>	<u>Typicals</u>
Specific Gravity	D1298	0.859
Color	D1500	L 1.0
Flash Point, °C	D92	246
Pour Point, °C	D97	-39
Viscosity, cSt. 40°C	D445	77
100°C		9.5
Viscosity Index	D2270	122
Neutralization No., mg KOH/gm	D664	1.5
Copper Strip Corrosion 3 hours @ 150°C	D130	1b
Evaporation Loss, wt% 22 hours @ 212°F	D972	0.5
Rust Test, distilled water	D665A	Pass
Rust Test, sea water	D665B	Pass
Wear prevention by four ball (scar, mm)	D4172	0.4

The World Leader in Fractional Horsepower Motor Lubrication