



255 East Brown Street, Ste 100, Birmingham, MI 48009

Phone: 248-433-3500 • Fax: 248-433-1824

Email: sales@permawick.com

<http://www.permawick.com>

Product: Vibex HP

Rev Level: 4

Rev Date: February 29, 2016

VIBEX-Plus Specification-Preliminary

1. Vibex-Plus Spec Details, Part N° PDG-016T and PDG-016P

Test Name	Method	Max	Typical	Min
Density, g/cm ³	ASTM D1298		1.55	
Brookfield Vis, 20 rpm @ 25°C	ASTM D2983			
Brookfield Vis, 100 rpm @ 25°C	ASTM D2983			
Cone Penetration	ASTM D217			
Water Resistance, % spray	ASTM D4049		Pass	
Flash Point, °C	ASTM D92			
Pour Point, °C	ASTM D97			
Oil Bleed Out, % weight	IPI 121		<0.1	0.15
Water resistance, 54.5°C (130°F), 22hrs	Internal		Pass	
Operating Temperature, °C		-30	25	60
Pounds/ gallon	Conversion		12.9	

Key characteristic are shown in red font

2. Recommended Temperature Range

-30°C to 60°C

3. Appearance

Dark gray

4. Packaging

Min Net Weight in pail.....29Kg (fills a 5 gallon or 18.92 Litre pail)

Min Net Weight in tube.....480 grams (fills a 310 ml tube)

5. Label Information

Vibex Part Number

Customer Part Number

Lot Number / Individual Container Number

Date of Manufacture