



255 East Brown Street, Ste 100, Birmingham, MI 48009

Phone: 248-433-3500 • Fax: 248-433-1824

Email: [sales@permawick.com](mailto:sales@permawick.com)

<http://www.permawick.com>

Product: Vibex HP

Rev Level: 4

Rev Date: February 29, 2016

## VIBEX-Sport Specification

### 1. Vibex-Sport Spec Details, Part N° PDG-007T and PDG-007P

Test Name	Method	Max	Typical	Min
Density, g/cm <sup>3</sup>	ASTM D1298		0.710	
Brookfield Vis, 20 rpm @ 25°C	ASTM D2983	600K	530K	470K
Brookfield Vis, 100 rpm @ 25°C	ASTM D2983	190K	150K	110K
Water Resistance, % spray	ASTM D4049		Pass	
Flash Point, °C	ASTM D92		280	260
Pour Point, °C	ASTM D97		-30	-25
Oil Bleed Out, % weight	IPI 121	0.20	<0.1	
Water resistance, 54.5°C (130°F), 22hrs	Internal		Pass	
Operating Temperature, °C		-30	25	60
Pounds/ gallon	Conversion		5.92	

Key characteristic are shown in green font

### 2. Recommended Temperature Range

-30°C to 60°C

### 3. Appearance

White

### 4. Packaging

Net Weight in pail.....14Kg (fills a 5 gallon or 18.92 Litre pail)

Net Weight in tube.....213g (fills a 310 ml tube)

### 5. Label Information

Vibex Part Number

Customer Part Number

Lot Number / Individual Container Number

Date of Manufacture