



PermaWick Company
255 E. Brown Street, Suite 100, Birmingham, MI 48009
Phone: 248-433-3500 • Fax: 248-594-3433
sales@permawick.com
www.permawick.com

An ISO9001 Certified Company

PD PSL 240

REV. # 1

REV. DATE: November 20, 2017

PSL240 OIL

POLYOLESTER BASED SYNTHETIC LUBRICANT FOR SINTERED METAL BEARINGS

DESCRIPTION

PERMAWICK PSL240 is a Polyolester based synthetic oil and fiber blend providing the ultimate in performance under the most grueling of conditions. Using the highest quality synthetic base stocks along with a sophisticated synergistic additive package, PermaWick PSL 240 is specially formulated for a long service life over a wide temperature range.

A flash point of 100 °F higher than conventional mineral oils provide an increased margin of safety. Low pour point and high viscosity index indicate excellent low temperature fluidity and pumpability.

PERMAWICK PSL240 OIL has a proven quality record and is specifically designed to meet the lubricating needs of FHP motor sleeve bearings.

PRODUCT FEATURES

- High film strength
- Low evaporation rate and oxidation resistant
- Very shear stable
- Resists rate of change of viscosity with temperature change
- Excellent anti-sludge and anti-varnish characteristics
- Wide temperature range: -40°F to 300°F (-40°C to 150°C)

<u>Performance Test</u>	<u>ASTM Method</u>	<u>Typical</u>
Specific Gravity	D1298	1.01
Color	D1500	2
Flash Point, °C	D92	283
Fire Point, °C	D92	327
Pour Point, °C	D97	-60
Viscosity, cSt. 40°C	D445	52
100°C		8.8
Viscosity Index	D2270	142
Neutralization No., mg KOH/gm	D664	0.01
Copper Strip Corrosion 3 hours @ 212°F	D130	1a
Evaporation Loss, wt% 22 hours @ 210°F	D972	<0.15
Falx pin and vee block, lbf	D3233(B)	1500

The World Leader in Fractional Horsepower Motor Lubrication