



PermaWick Company
 255 E. Brown Street, Suite 100, Birmingham, MI 48009
 Phone: 248-433-3500 • Fax: 248-594-3433
 sales@permaWick.com
 www.permaWick.com

An ISO9001 Certified Company
 PD PSL 400
 REV. # 3
 REV. DATE: June 6, 2017

PSL400 OIL
POLYOLESTER BASED SYNTHETIC LUBRICANT FOR SINTERED METAL BEARINGS

DESCRIPTION

PERMAWICK PSL400 a Polyolester based synthetic oil providing the ultimate in performance under the most grueling of conditions. Using the highest quality synthetic base stocks along with a sophisticated synergistic additive package, PSL400 PermaWick is specially formulated for a long service life over a wide temperature range.

A flash point of 40°C higher than conventional mineral oils provides an increased margin of safety. Low pour point and high viscosity index indicate excellent low temperature fluidity and pumpability.

PERMAWICK PSL400 OIL is specifically designed to meet the lubricating needs of FHP motor sleeve bearings.

PRODUCT FEATURES

- High film strength
- Low evaporation rate and oxidation resistant
- Very shear stable
- Resists rate of change of viscosity with temperature change
- Excellent anti-sludge and anti-varnish characteristics
- Useful temperature range: -40°F to 300°F (-40°C to 150°C)

<u>Performance Test</u>	<u>ASTM Method</u>	<u>Typicals</u>
Gravity, API	D1298	9.44
Specific Gravity	D1298	1.004
Flash Point, °C	D92	249
Fire Point, °C	D92	295
Pour Point, °C	D97	-46
Viscosity, cSt.	D445	-20°C
		0°C
		40°C
		100°C
Viscosity, SUS	D88	390
Viscosity Index	D2270	176
Copper Strip Corrosion	D130	1a

The World Leader in Fractional Horsepower Motor Lubrication

PermaWick Product Data Sheet