



## Permawick Company

3110 Permawick Drive, Columbus, Indiana 47201

Phone: 812-376-0703 • Fax: 812-372-1410

sales@permawick.com

www.permawick.com

**An ISO9001 Certified Company**

PD 284C

REV. # 1

REV. DATE: March 21, 2022

### 284C OIL (Anti Corrosion Oil)

Mineral Based Lubricant for Rust Preventative Applications

#### DESCRIPTION

PERMAWICK 284C OIL is formulated to provide superior performance where corrosion and high humidity are of primary concern. Solvent extracted and hydro-treated base stocks were selected to give greater oxidation stability and a higher viscosity index. Special oxidation inhibitors have been added to counteract varnish and sludge formation while select additives protect against rust, corrosion, and wear.

#### PRODUCT FEATURES

- Specifically formulated to have excellent protection against rust and corrosion
- For use in applications requiring superior metal protection in 100% humidity as well as harsh salt environments.
- Cost effective mineral oil formulation
- Shear stable
- Superior low temperature fluidity properties
- High viscosity index reduces excessive oil thinning at high temperature
- Useful temperature range: -30°C to 95°C

<u>Performance Test</u>	<u>ASTM Method</u>	<u>Typical Values</u>
Specific Gravity	D1298	0.881
Color	D1500	3.5
Flash Point, °C	D92	213
Fire Point, °C	D92	249
Pour Point, °C	D97	-38
Viscosity, cSt. 40°C	D445	106.6
100°C		13.36
Viscosity Index	D2270	122.8
Copper Strip Corrosion 3 hours @ 100°C	D130	1C Max
Evaporation Loss, wt. % 22 hours @ 98.9°C	D972	<1.0
<b>Rust protection</b>	<b>D665(B)</b>	<b>Pass</b>
<b>Rust protection (Salt fog chamber, 24hrs)</b>	<b>B117</b>	<b>Pass</b>