



PermaWick Company
 255 E. Brown Street, Suite 100, Birmingham, MI 48009
 Phone: 248-433-3500 • Fax: 248-594-3433
 sales@permaWick.com
 www.permaWick.com

An ISO9001 Certified Company
 PD P2AO 150
 REV. # 4
 REV. DATE: May 25, 2017

P2AO150 OIL
PAO BASED SYNTHETIC LUBRICANT FOR SINTERED METAL BEARINGS

DESCRIPTION

PERMAWICK P2AO150 OIL is especially developed for plastic compatibility for use in the fractional horsepower electric motor industry. This lubricant possesses extremely long service life and resists any leakage or washing away that could cause dry running. Low pour point and high viscosity index provide superior low temperature fluidity.

PERMAWICK P2AO150 OIL is hydrolytically stable oil with remarkable thermal and chemical stability and has a wide use range of -40 to 125°C.

PRODUCT FEATURES

- Oxidation and corrosion resistant
- Reduced rate of change of viscosity with temperature change
- Separates easily from water
- Mixes with conventional mineral oils
- Reduces friction and wear

<u>Performance Test</u>	<u>ASTM Method</u>	<u>Typicals</u>
Specific Gravity	D1298	0.827
Color	D1500	<1.0
Flash Point, °C	D92	246
Pour Point, °C	D97	-54
Viscosity, cSt. 40°C	D445	24
100°C		5.1
Viscosity Index	D2270	147
Neutralization No., mg KOH/gm	D664	0.01
Copper Corrosion		
3 hours @ 100°C	D130	1a
Evaporation Loss, % mass, grams		
22 hours @ 100°C	D972	0.2
Rust Protection, sea water	D665	Pass

The World Leader in Fractional Horsepower Motor Lubrication

PermaWick Product Data Sheet