



**PermaWick Company**  
255 E. Brown Street, Suite 100, Birmingham, MI 48009  
Phone: 248-433-3500 • Fax: 248-594-3433  
sales@permaWick.com  
www.permaWick.com

**An ISO9001 Certified Company**  
PD P2AO 151  
REV. # 3  
REV. DATE: May 25, 2017

**P2AO151 OIL**  
**PAO BASED SYNTHETIC LUBRICANT FOR SINTERED METAL BEARINGS**

**DESCRIPTION**

PERMAWICK P2AO151 OIL is especially developed for plastic compatibility for use in the fractional horsepower electric motor industry. This lubricant possesses extremely long service life and resists any leakage or washing away that could cause dry running. Low pour point and high viscosity index provide superior low temperature fluidity.

PERMAWICK P2AO151 OIL is hydrolytically stable oil with remarkable thermal and chemical stability and has a wide use range of -40 to 125°C.

**PRODUCT FEATURES**

- Oxidation and corrosion resistant
- Reduced rate of change of viscosity with temperature change
- Separates easily from water
- Mixes with conventional mineral oils
- Reduces friction and wear

<b><u>Performance Test</u></b>	<b><u>ASTM Method</u></b>	<b><u>Typicals</u></b>
ISO VG	D445	32
Specific Gravity	D1298	0.827
Color	D1500	<1.0
Flash Point, °C	D92	246
Pour Point, °C	D97	-54
Viscosity, cSt. 40°C	D445	31
100°C		5.8
Viscosity Index	D2270	138
Neutralization No., mg KOH/gm	D664	0.01
Copper Corrosion		
3 hours @ 100°C	D130	1a
Evaporation Loss, % mass, grams		
22 hours @ 100°C	D972	0.2
Rust Protection, sea water	D665	Pass

**The World Leader in Fractional Horsepower Motor Lubrication**