



PermaWick Company
 255 E. Brown Street, Suite 100, Birmingham, MI 48009
 Phone: 248-433-3500 • Fax: 248-594-3433
 sales@permawick.com
 www.permawick.com

An ISO9001 Certified Company
 PD P2AO 350PG
 REV. # 5
 REV. DATE: May 30, 2017

P2AO350PG PERMAGEL
PAO BASED SYNTHETIC LUBRICANT FOR SINTERED METAL BEARINGS

DESCRIPTION

P2AO350 PERMAGEL is especially developed for plastic compatibility for use in the fractional horsepower electric motor industry.

Automotive applications: Wipers, window lifts, seat motors, blowers, radiator cooling fans, all small sintered metal bearing motors

High-temp applications: pump motors requiring longer life, exhaust fans, tube axial fans, computer fans

PRODUCT FEATURES

- Long service life
- Corrosion and oxidation resistant
- Low evaporation
- Low pour and high VI indicate excellent low temperature fluidity characteristics
- Shear stable
- Excellent anti-wear performance
- Useful temperature range: -40°C to 125°C

<u>Performance Test: Permugel</u>	<u>ASTM Method</u>	<u>Typicals</u>
Base Oil		P2AO 350
Penetration (60 strokes, 25°C)	D217	NLGI #3
Color	Visual	Translucent, Yellow
Drop Point	D566	Without
Density		0.99
Copper Corrosion @ 100°C	D4048	1b
Pounds/Gallon		8.25
Structure		Homogenous

<u>Performance Test: Base Oil</u>	<u>ASTM Method</u>	<u>Typicals</u>
Specific Gravity	D1298	0.8373
Flash Point, °F	D92	250
Pour Point, °F	D97	<-60
Viscosity, cSt. 40°F	D445	75.78
100°F		11.76
Viscosity Index	D2270	160
Neutralization No., mg KOH/gm	D664	0.01
Evaporation Loss, % mass, grams 22 hours @ 210°F	D972	0.4

The World Leader in Fractional Horsepower Motor Lubrication