



PermaWick Company
 255 E. Brown Street, Suite 100, Birmingham, MI 48009
 Phone: 248-433-3500 • Fax: 248-594-3433
 sales@permaWick.com
 www.permaWick.com

An ISO9001 Certified Company
 PD P2AO 40
 REV. # 4
 REV. DATE: May 23, 2017

P2AO40
PAO BASED SYNTHETIC LUBRICANT FOR SINTERED METAL BEARINGS

DESCRIPTION

PERMAWICK P2AO40 OIL is a member of a high performance line of lubricants developed for plastic compatibility in the fractional horsepower electric motor industry. These synthetics have excellent low temperature pumpability, corrosion resistance, and oxidation stability.

PERMAWICK P2AO OILS excel in low temperature applications and whenever ISO VG 5 oils are indicated especially in high speed applications.

PRODUCT FEATURES

- Long service life with excellent lubricating qualities
- Non-staining
- Separates readily from water
- Soluble in conventional mineral oils
- Reduced rate of change of viscosity with temperature change
- Useful temperature range: <-45°C to 50°C

<u>Performance Test</u>	<u>ASTM Method</u>	<u>Typicals</u>
Gravity, API, (Degrees)	D1298	44.7
Specific Gravity	D1298	0.803
Color	D1500	0.5
Flash Point, °C	D92	160
Fire Point, °C	D92	180
Pour Point, °C	D97	<-65
Viscosity, cSt.	D445	40°C
		100°C
Viscosity, SUS	D445	100°F
		210°F
		210°F
Neutralization No., mg KOH/gm	D664	0.01
Copper Strip Corrosion	D130	3 hours @ 100°C
		3 hours @ 100°C
Evaporation Loss, % mass, grams	D972	22 hours @ 100°C
		22 hours @ 100°C