



255 East Brown Street, Ste 100, Birmingham, MI 48009

Phone: 248-433-3500 • Fax: 248-433-1824

Email: sales@permawick.com

<http://www.permawick.com>

Product: Vibex Plus

Rev Level: A

Rev Date: May 31, 2016

VIBEX-Plus Specification

1. Vibex-Plus Spec Details, Part N° PDG016T and PDG016P

Test Name	Method	Max	Typical	Min
Density, g/cm ³	ASTM D1298		1.49	
Brookfield Vis, 20 rpm @ 25°C	ASTM D2983	600K	475K	350K
Brookfield Vis, 100 rpm @ 25°C	ASTM D2983	200K	140	80K
Water Resistance, % spray	ASTM D4049		Pass	
Flash Point, °C	ASTM D92		280	260
Pour Point, °C	ASTM D97		-30	-25
Oil Bleed Out, % weight	IPI 121		<0.1	0.15
Water resistance, 54.5°C, 22hrs	Internal		Pass	
Pounds/ gallon	Conversion		12.43	

Key characteristic are shown in red font

2. Recommended Temperature Range

-30°C to 60°C

3. Appearance

Gray with dispersed red particle

4. Packaging

Net Weight in pail.....27.2 Kg (60 lbs) (fills a 5 gallon or 18.92 liter pail)
(Or Customer specified lower weight)

5. Label Information

Permawick Part Number

Vibex Part Number

Customer Part Number

Lot Number / Individual Container Number

Date of Manufacture

Quantity (Net Weight)

Color Coding